

Data Sheet

Fujitsu Display B19-6 LED Displays

Advanced display: 48.3 cm (19-inch)
Best ergonomic and energy saving solutions for office applications

The B19-6 LED offers best ergonomics and usability for intensive office use with a 4-in-1 stand.

Environment-friendly LED technology with unique, high efficient energy saving solutions like ECO operation mode and ECO standby

Convenient and fatigue-proof longtime-usage with excellent visual ergonomics for the office

Optimized and relaxed position - with ergonomic stand featuring height adjust, swivel, tilt and 90° rotation

Flexible connectivity with DVI and Analog

Ready for remote inventory and administration tasks due to the DisplayView Manageability tools

Representative design with space saving front frame and smart details like discretely integrated speakers



Technical details

Special features

4-in-1 Stand, Eco button for Eco mode and 3-coloured Eco status LED, Pivot, DisplayView™ IT Suite, 24/7 usage

Ergonomic stand

Stand	4-in-1 Stand
Height adjust range	110 mm
Picture height over desk (min)	55 mm
Rotation to portrait	90°
Tilt angle	-5° / +35°
Swivel angle	340°

Picture performance

Panel and backlit	TN/LED
Contrast - typical	1000:1
Contrast - advanced	2,000,000:1
Response time typical	5 ms
Viewing angle (h/v) - typical	170°/170° CR5:1
Color performance	16.7 million colors (Hi-FRC)
Brightness - typical	250 cd/m2

Size and resolution

Aspect ratio	5:4
Diagonal Size	48.3 cm (19-inch)
Resolution (native)	1280 x 1024 pixel (recommended)
Resolution (interpolated)	1024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	376 x 301 mm
Pixel Pitch	0.294 mm

Frequencies

Horizontal	30 - 82 kHz
Vertical	56 - 76 Hz

Connectivity

DVI	1 x DVI (HDCP)
VGA/D-SUB	1 x D-SUB
Audio signal input	3.5 mm stereo phone jack
Audio sound output	2 x 1 W

Ease-of-use menu

Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese
Brightness / Contrast	Brightness, Contrast, Black level, Auto level
Color	sRGB, 6500K, 7500K, 9300K, Native, Custom Color (R,G,B)
Image adjust	Clock, Phase, H-Position, V-Position, Expansion
Audio	Mute, Volume
Information	Model name, S/N, Resolution/mode, Signal input
Setup	Input select, Language, DDC-CI, OSD-Timeout, Factory recall

Power consumption (typical)

Soft switch off	0.1 W
Power save mode	0.1 W
Operating with EPA settings	19 W
Operating maximum brightness	25 W
Power supply display	integrated
Power notes	without sound;

Electrical values

Rated voltage range	100 V - 240 V
---------------------	---------------

Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Europe	CE certification according to EC Directive 2004/108/EEC, EN 60950, Nordic Swan, RoHS, WEEE, IT-Eco-Declaration, EN 60601-1-2
Model	B19-6
Germany	TÜV GS
Russia	GOST
USA/Canada	FCC Class B, cUL
Japan	VCCI
South Korea	KC
Argentina	TÜV-S
China	CCC (AC-Adapter)
Saudi Arabia	SASO
Mexico	NOM
Global	TCO Displays 5.1, ENERGY STAR® 5.0, EPEAT® Gold (dedicated regions), ISO9241-307 (Pixel fault class I)
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Quality and Reliability	
MTBF (demonstrated)	70000 h
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	411 x 58 x 348 mm
Dimension with stand (W x D x H)	411 x 180 x 374 mm
Weight (packed)	6.5 kg
Weight (unpacked)	5.0 kg
Weight (Monitor only)	2.8 kg
Operating ambient temperature	5 - 35 °C
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Marble grey
Package content	
Display delivered accessories	DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet
Display delivered accessories notes	Data cables and audio cable detachable on display
Order information	
Order Code	S26361-K1374-V140
EAN Code	4049699310645
Warranty	
Standard Warranty	3 years (depending on country)
Service level	Collect & Return Service (depending on country specific requirements)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support



red dot design award winner
2011

Design of Fujitsu Displays P, B
and E Line, International - March
15, 2011

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu Display B19-6 LED, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu Display B19-6 LED, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/fts/displays>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions
Website: www.fujitsu.com/fts
2013-07-29 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions